

	<b>Bait Al Batterjee Medical Trading Co.</b>
	Saudi German Hospital Group
	Al Zahra Dist. Jeddah
	Tel. No. 02 – 6620 296 / 6620 396 / 6620 279 Ext: 5029
	Fax No. 02 – 256 2973
	Direct Line 02 - 6905129

<b>Date : 15 / 09 / 2008</b>	<b>Contact Person : Dr. Alaa El Shreef - Dr. Mohy khalil</b>
<b>Pages : 1 : 25</b>	<b>E mail Address : <a href="mailto:xrav1.jed@sghgroup.net">xrav1.jed@sghgroup.net</a> - <a href="mailto:bab@sghgroup.net">bab@sghgroup.net</a></b>
<b>Vender :</b>	<b>Mobile : 00966 505 640 079 - 00966 561 052 512</b>
<b>Attention : Sales Manager</b>	
<b>Enclosed please find our Tender Document for <a href="#">DAY SURGERY DEPARTMENT</a></b>	
<b>Please submit your best prices for the following items complete specification, Catalogue copy &amp; C.V for units</b>	
<b>Your offer in witting should reach to the undersign before 15 / Dec / 2008</b>	
<b>You may quote your equivalent product if you are unable to offer the specification item</b>	

### **General Requirements for the Negotiable Tender**

- 1- The Manufacture has to offer the Highest & Latest model in the required Item with all the Encouraging specification which let the dean of the tender to choose the Product.
- 2- The offer must contain all Hardware & Software available At time of tender.
- 3- The Manufacture will apply all the Upgrade will be added to the unit Free of Charge.
- 4- The Manufacture will offer clear C.V of the Same Model in his quotation with year of production.
- 5- Warrantee is (5) years including labor & Spare parts & Accessories needed for the perfect work of the unit.
- 6- The Manufacture will assure the wok of the unit during the Warrantee with Minimum of 320 days / Year.
- 7- It will be Service Contract for (5) years after the warrantee period in the offer of the manufacturer.
- 8- It's better for the Manufacturer to offer Basic Unit & alternative for each item.
- 9- It's well known that The Company which will win the Tender is going to Sign the Contract with SGH Group.
- 10- This Contract Details will be Discusses with the Company after The Evaluation with the whole Higher Management SGH Group.
- 11- The specification in the book is the nearly accepted but not restricted so each Company Can offer the best Models which Help doctors & Staff to Offer the Best Benefits for the Patient.

**Dr. MOHY KHALIL**  
**[bab@sghgroup.net](mailto:bab@sghgroup.net)**

## INDEX

### DEPARTMENT: DAY SURGEY

S.No	Items Descriptions	Qty	No. of pages	Manufacture	Origin	Model	Unit Price	Total Price
1	OR CELING LIGHT BLUE 130 WITH 3 DOM WITH CAMERA PROVISION WITH ALL ACCESS.	4	1					
2	PENDANT CEILING DOUBLE ARM S ONE FULL MOVABLE SPRING ARM FOR SURGERY AND ONE FOR ANAESTHESIA SIDE WITH ALL ACCESS. HERAEUS	4	1					
3	PENDANT CEILING SINGLE ARM BETA WITH ALL ACCESS	2	1					
4	SCRUB UP SINK FOR 4 PERSON KNEE OPERATING.	2	1					
5	DISPENSER SYSTEM F/NAIL BURSHESSMADE OF CHROM-NICKEL STEEL, FIXING ON THE WALL MARTIN	10	1					
6	X-RAY VIEWER 80×43 CM	6	1					
7	OR TABLE COLUMN MOBILE.	2	1					
8	MODULAR UNIVERSAL TABLE TOP	4	1					
9	TRANSPORTER TROLLEY FOR TABLE TOP	3	1					
10	ALPHASTAR MOBILE OPERATING ROOM TABLE WITH ACCESSORIES	2	1					
11	ALPHACLASIC MOBILE OPERATING ROOM TABLE WITH ACCESSORIES	2	1					
12	MAYO INSTRUMENT TABLE	4	1					
13	INSTRUMENT TABLE	16	1					
14	FOOT STEP DOUBLE	10						
15	FOOT STEP SINGLE	10	1					
16	BOWL STAND WITH HEATER	4	1					
17	KICK BUCKET	10	1					
18	ELECTROSURGICAL CAUTARY MACHINE WITH CART	1	1					
19	STEAM STERILIZER ECOSTE 101 SINGLE DOOR WITH ALL ACCESS	1	1					
20	OR CELING LIGHT BLUE 90 SINGLE SATELLITE WITH ALL ACCESS	5	1					
21	ERBOTOM ICC 200 ENDO- CUT WITH CART	6	1					
22	INSTRUMENT TROLLEY	3	1					
23	SEPTIC FLUID SCUTION PUMP WITH TROLLEY	1	1					

**OR CELING LIGHT BLUE 130 WITH 3 DOM WITH CAMERA PROVISION  
WITH ALL ACCESS.**

**ITEM NO: 1**

Specification For : <b>OR CELING LIGHT BLUE 130 WITH 3 DOM WITH CAMERA PROVISION WITH ALL ACCESS.</b>	<b>QTY</b>
<p align="center"><b>OR CELING LIGHT BLUE 130 WITH 3 DOM WITH CAMERA PROVISION WITH ALL ACCESS.</b></p> <ul style="list-style-type: none"> <li>- Illumination 120,000 Lux x 100,000 Lux</li> <li>- Diameter of satellite excluding handles: 900 mm x 510 mm</li> <li>- Number of prisms: 4 355 x 2 184</li> <li>- Diameter of large field: 28 cm x 17 cm</li> <li>- Diameter of small field: 20 cm x 14 cm</li> <li>- Depth of the volume of light: 80 cm x 80 cm</li> <li>- Color rendering index (IRC): 95 +/- 2 Ra x 95 +/- 2 Ra</li> <li>- Color Temperature: 3300 K (+/- 200) x 3300</li> <li>- Infrared filtratin: Absorbent + dichroic x absorbent Athermal filters</li> <li>- Radiant energy: 4.5 x 5.5 mW/m<sup>2</sup>.Lux</li> <li>- Input power: 375 x 125 VA</li> <li>- Low voltage consumption: 12 x 4 A</li> <li>- Voltage at bulb terminals: 23V x 23 V</li> <li>- Number of halogen bulbs 24V/100 W: 3 x 1</li> <li>- Minimum height of room for clearance of 2880 mm</li> <li>- Positioning range of satellite: 12280 mm</li> <li>- Maximum reaction torque of configuration: 141 m.DaN</li> <li>- Voltage: <b>110V- 220V 60 Hz</b></li> </ul>	<b>4</b>

**PENDANT CEILING DOUBLE ARM S ONE FULL MOVABLE SPRING ARM  
FOR SURGERY AND ONE FOR ANAESTHESIA SIDE WITH ALL ACCESS.  
HERAEUS**

**ITEM NO: 2**

<p align="center"><b>Specification For : PENDANT CEILING DOUBLE ARM S ONE FULL MOVABLE SPRING ARM FOR SURGERY AND ONE FOR ANAESTHESIA SIDE WITH ALL ACCESS. HERAEUS</b></p>	<p align="center"><b>QTY</b></p>
<p align="center"><b><u>PENDANT CEILING DOUBLE ARM S ONE FULL MOVABLE SPRING ARM FOR SURGERY AND ONE FOR ANAESTHESIA SIDE WITH ALL ACCESS. HERAEUS</u></b></p> <ul style="list-style-type: none"> <li>- Parking and working position are fundamentally different</li> <li>- Speedier change-over of medial equipment and instruments</li> <li>- Quick, easy swiveling in case of emergency</li> <li>- Supply of high and low tension current as well as medical gases to the surgical instruments.</li> <li>- Clearance height of 2 m</li> <li>- Modular equipping of appliances of differing weights and sizes</li> <li>- Variable work positions when patients are brought in and out of anesthesia areas.</li> <li>- The basic components consist of: Box, Shelves, Drawers, Keyboard/writing drawers, Tilt/Swivel section, I.V Poles, docking/lifting system for apparatus, Electrical connections, Medical gas connection, special apparatus, communication and data lines.</li> <li>- Air motor</li> <li>- Voltage: <b>110V- 220V 60 Hz</b></li> </ul>	<p align="center"><b>4</b></p>

**PENDANT CEILING SINGLE ARM BETA WITH ALL ACCESS****ITEM NO: 3**

Specification For: <b>PENDANT CEILING SINGLE ARM BETA WITH ALL ACCESS</b>	<b>QTY</b>
<p style="text-align: center;"><b><u>PENDANT CEILING SINGLE ARM BETA WITH ALL ACCESS</u></b></p> <ul style="list-style-type: none"> <li>- Parking and working position are fundamentally different</li> <li>- Speedier change-over of medial equipment and instruments</li> <li>- Quick, easy swiveling in case of emergency</li> <li>- Supply of high and low tension current as well as medical gases to the surgical instruments.</li> <li>- Clearance height of 2 m</li> <li>- Modular equipping of appliances of differing weights and sizes</li> <li>- Variable work positions when patients are brought in and out.</li> <li>- The basic components consist of: Box, Shelves, Drawers, Keyboard/writing drawers, Tilt/Swivel section, I.V Poles, docking/lifting system for apparatus, Electrical connections, Medical gas connection, special apparatus, communication and data lines.</li> <li>- Air motor</li> <li>- Voltage: <b>110V- 220V 60 Hz</b></li> </ul>	<b>2</b>

**SCRUB UP SINK FOR 4 PERSON KNE OPERATING.****ITEM NO: 4**

Specification For: <b>SCRUB UP SINK FOR 4 PERSON KNE OPERATING.</b>	<b>QTY</b>
<p style="text-align: center;"><b><u>SCRUB UP SINK FOR 4 PERSON KNE OPERATING.</u></b></p> <ul style="list-style-type: none"> <li>- Scrub up unit chrome nickel steel 18/10, drainage channel uninterrupted each with gradient to the drainage, Drainage set with sieve valve and complete drainage pipe work to a central point. Back wall 110 mm deep, constructed as installation panel, completely with supply pipe work and installation for operating fittings. Sloping front bottom with extensive removable revision covers, protected by box spanner lock-mechanism.</li> <li>- Including 2 built-in thermostat, 4 outlet arm and 4 built-in hip operated valve</li> <li>- Dimension: W x D x H 3500mm x 540mm x 1000mm</li> <li>- Voltage: <b>110V- 220V 60 Hz</b></li> </ul>	<b>2</b>

**DISPENSER SYSTEM F/NAIL BURSHESSMADE OF CHROM-NICKEL STEEL,  
FIXING ON THE WALL MARTIN**

**ITEM NO: 5**

Specification For: <b>DISPENSER SYSTEM F/NAIL BURSHESSMADE OF CHROM-NICKEL STEEL, FIXING ON THE WALL MARTIN</b>	<b>QTY</b>
<p align="center"><b><u>DISPENSER SYSTEM F/NAIL BURSHESSMADE OF CHROM-NICKEL STEEL, FIXING ON THE WALL MARTIN</u></b></p> <p>- Dispenser for 20 brushes with suspension hook Size: 260x300x65 mm</p>	<b>10</b>

**X-RAY VIEWER 80×43 CM****ITEM NO: 6**

Specification For: <b>X-RAY VIEWER 80×43 CM</b>	<b>QTY</b>
<p data-bbox="544 524 932 560" style="text-align: center;"><b><u>X-RAY VIEWER 80×43 CM</u></b></p> <ul data-bbox="199 589 1225 763" style="list-style-type: none"><li>- To built-in wall with surrounding frame to cover the joint, Viewing area with 3 daylight fluorescent tubes of 30 Watts each, with electronic stepless brightness control</li><li>- Max. Luminous density : 2400 – 3600 cd/sq m</li><li>- Dimension: 1000 x 625 x 102 mm W x H x D</li><li>- Power input in Watt: 110, Current in ampere: 1.1</li><li>- Voltage: <b>110V- 220V 60 Hz</b></li></ul>	<b>6</b>

**OR TABLE COLUMN MOBILE.****ITEM NO: 7**

Specification For: <b>OR TABLE COLUMN MOBILE.</b>	<b>QTY</b>
<p data-bbox="448 533 983 573" style="text-align: center;"><b><u>OR TABLE COLUMN MOBILE.</u></b></p> <ul data-bbox="199 600 1262 869" style="list-style-type: none"><li>- The column movement –490 mm of vertical stroke, +/- 40° of trendelenburg/reverse trendelenburg adjustment, +/- 27° of lateral tilt. The control electronics feature automatic return to the 0-position.</li><li>- On a flat base, the transporter can lift, move and set down the column and table top at any desired location, special design, maintenance free batteries and electronic charge control are integrated into the base.</li><li>- Electromechanical, battery powered, movable with transporter, including IR transmitter mobile charging unit.</li><li>- Voltage: <b>110V-220V 60 Hz</b></li></ul>	<b>2</b>

**MODULAR UNIVERSAL TABLE TOP****ITEM NO: 8**

Specification For: <b>MODULAR UNIVERSAL TABLE TOP</b>	<b>QTY</b>
<p style="text-align: center;"><b><u>MODULAR UNIVERSAL TABLE TOP</u></b></p> <ul style="list-style-type: none"> <li>- Maximum of 6 subdivisions- head plate, upper back, lower back, seat plate and split let plates. Motor-powered table top adjustments providing 275 mm of longitudinal shift, lower back up/down, leg plates up/down, either simultaneously or individually. Manual adjustment to raise/lower back plate and 60 mm of longitudinal extension.</li> <li>- With external table top control, PUR padded, with Standard back plate for general surgery, PUR padded, Head rest with double articulation tilt able with cassette rails, PUR padded, Leg plates (coded) with double-joint abduction, PUR padded.</li> </ul>	<b>4</b>

**TRANSPORTER TROLLEYFOR TABLE TOP****ITEM NO: 9**

Specification For: <b>TRANSPORTER TROLLEYFOR TABLE TOP</b>	<b>QTY</b>
<p data-bbox="397 600 1078 633" style="text-align: center;"><b><u>TRANSPORTER TROLLEYB FOR TABLE TOP</u></b></p> <ul data-bbox="199 665 1254 781" style="list-style-type: none"><li>- Made from CrNi steel and an aluminum alloy, can be moved longitudinally and laterally with four tandem swivel castor, two of which can be locked centrally at the left and right front castors can also be fixed individually. Additional stabilization castor at the side for straight-line travel.</li></ul>	<b>3</b>

**ALPHASTAR MOBILE OPERATING ROOM TABLE WITH ACCESSORIES****ITEM NO: 10**

Specification For: <b>ALPHASTAR MOBILE OPERATING ROOM TABLE WITH ACCESSORIES</b>	<b>QTY</b>
<p><b><u>ALPHASTAR MOBILE OPERATING ROOM TABLE WITH ACCESSORIES</u></b></p> <ul style="list-style-type: none"> <li>- Mobile operating table with electro-Hydraulic Foot operated pedal-powered actuation for the basic functions- height, lateral tilt and Trendelenburg/reverse Trendelenburg position- 5 section operating table top.</li> <li>- Table top frame and column casing made entirely of CrNi steel. Base cover manufactured from a rugged, high-impact composite material, resistant to fractures and disinfectant. Guide rails below the back and seat plates allow for insertion of x-ray cassettes from the head through to the pelvis.</li> <li>- The operating table is mobile on 4 large castors of 125 mm diameter and can be locked by means of double swivel castors at the head end by using a central pedal.</li> <li>- Length without head rest: 1800 mm</li> <li>- Length with head rest: 2080 mm</li> <li>- Width of table Top: 510 mm</li> <li>- Width measured across side rails: 560 mm</li> <li>- Height, including padding: 650 to 1000 mm</li> <li>- Trendelenburg and reverse Trendelenburg: 25°</li> <li>- Lateral tilt left /right: 15°</li> <li>- Back plate upward/downward: 60°/50°</li> <li>- Leg plate downward: 100°</li> <li>- Weight: 180 kg</li> <li>- Voltage: <b>110V- 220V 60 Hz</b></li> </ul>	<b>2</b>

**ALPHA CLASIC MOBILE OPERATING ROOM TABLE WITH ACCESSORIES****ITEM NO: 11**

Specification For: <b>ALPHA CLASIC MOBILE OPERATING ROOM TABLE WITH ACCESSORIES</b>	<b>QTY</b>
<p><b><u>ALPHA CLASIC MOBILE OPERATING ROOM TABLE WITH ACCESSORIES</u></b></p> <ul style="list-style-type: none"> <li>- Mobile operating table electrically controlled hydraulic drive, storage battery and line power supply. Electrical, hydraulically powered functions operated via corded hand control or infrared remote control. Solid, stable base construction with four double swivel castor for easy motion and maneuvering of the operating table.</li> <li>- Table top frame made of cast aluminum with wear-proof and disinfectant proof enamel. Base and column head cover made of special, fiber grass reinforced laminate- resistant to impact, breakage and disinfectants. Center column casing joint covers and side rail equipment for the table top made of chrome-nickel steel.</li> <li>- Operating table top subdivided into a maximum of 6 sections: head rest, two extension segments, normal back, seat plate, short REVERSE back (leg plat). The head rest, the entire back plate, the foot end of the seat plate and the leg plate of the operating table top are designed without crossbars to allow for radiography during surgical interventions. Guide rails beneath the table top allow for inserting X-ray cassettes from the head and foot end.</li> <li>- The operating table is mobile on 4 large castors of 125 mm diameter and can be locked by means of double swivel castors at the head end by using a central pedal.</li> <li>- Length without head rest: 1550 mm</li> <li>- Length with head rest: 2095 mm</li> <li>- Width of table Top: 520 mm</li> <li>- Width measured across side rails: 590 mm</li> <li>- Height, including padding: 685 to 1125 mm</li> <li>- Trendelenburg and reverse Trendelenburg: 30°</li> <li>- Lateral tilt left /right: 18°</li> <li>- Back plate upward/downward: 68°/25°</li> <li>- Leg plate downward: 80°/105°</li> <li>- Weight: 300 kg</li> <li>- Voltage: <b>110V- 220V 60 Hz</b></li> </ul>	<b>2</b>

**MAYO INSTRUMENT TABLE.****ITEM NO: 12**

Specification For: <b>MAYO INSTRUMENT TABLE.</b>	<b>QTY</b>
<p data-bbox="491 600 938 636" style="text-align: center;"><b><u>MAYO INSTRUMENT TABLE.</u></b></p> <ul data-bbox="199 667 1257 788" style="list-style-type: none"><li>- Integral precision hydraulic pump. Base and lift column made of 18/10 CrNi steel.</li><li>- Height adjustable via pump pedal coated with electrically conductive rubber compound.</li><li>- Plate dimension: Length: 700 mm, Width: 500 mm Height adjustable: 900-1350 mm</li><li>- Weight: 38 kg.</li></ul>	<b>4</b>

**INSTRUMENT TABLE.****ITEM NO: 13**

Specification For: <b>INSTRUMENT TABLE.</b>	<b>QTY</b>
<p data-bbox="549 593 884 627" style="text-align: center;"><b><u>INSTRUMENT TABLE.</u></b></p> <ul data-bbox="199 658 1166 779" style="list-style-type: none"><li>- Mobile 4-leg frame construction made of 18/10 CrNi steel with 2 plates.</li><li>- 4- plastic swivel castors, wear-resistant, non-discoloring, electrically conductive.</li><li>- Length: 635 mm, Width: 435 mm, Height: 900 mm</li><li>- Weight: 12 kg.</li></ul>	<b>16</b>

**FOOT STEP DOUBLE.****ITEM NO: 14**

Specification For: <b>FOOT STEP DOUBLE.</b>	<b>QTY</b>
<p data-bbox="555 521 879 555" style="text-align: center;"><b><u>FOOT STEP DOUBLE.</u></b></p> <ul data-bbox="199 589 871 734" style="list-style-type: none"><li>- Stable four-leg design, made of 18/10 steel</li><li>- Tread is ribbed and slip-resistant.</li><li>- Electrically conductive rubber feet.</li><li>- Length: 600 mm, Width: 650 mm Height: 220/440 mm</li><li>- Weight: 14kg.</li></ul>	<b>10</b>

**FOOT STEP SINGLE.****ITEM NO: 15**

Specification For: <b>FOOT STEP SINGLE.</b>	<b>QTY</b>
<p data-bbox="560 521 871 560" style="text-align: center;"><b><u>FOOT STEP SINGLE.</u></b></p> <ul data-bbox="201 589 820 734" style="list-style-type: none"><li>- Stable four-leg design, made of 18/10 steel</li><li>- Tread is ribbed and slip-resistant.</li><li>- Electrically conductive rubber feet.</li><li>- Length: 600 mm, Width: 350 mm Height: 130 mm</li><li>- Weight: 7 kg.</li></ul>	<b>10</b>

**BOWL STAND WITH HEATER.****ITEM NO: 16**

Specification For: <b>BOWL STAND WITH HEATER.</b>	<b>QTY</b>
<p data-bbox="486 555 944 591" style="text-align: center;"><b><u>BOWL STAND WITH HEATER.</u></b></p> <ul data-bbox="199 622 1241 891" style="list-style-type: none"><li>- Mobile, five-leg resist design made of 18/10 CrNi steel.</li><li>- Painted cast housing with heating element and integral safety thermostat limiting temperature to 60°C.</li><li>- Five plastic swivel castors, wear-resistant, non-discolouring when in contact with other material, electrically conductive, 75 mm diam. With lint and thread shield, two castors with locking brakes.</li><li>- Diameter: 400 mm, Height adjustment: 920-1290 mm</li><li>- Weight: 12.5 kg.</li><li>- Voltage: <b>110V-220V 60 Hz</b></li></ul>	<b>4</b>

**KICK BUCKET.****ITEM NO: 17**

Specification For: <b>KICK BUCKET.</b>	<b>QTY</b>
<p data-bbox="598 521 831 555" style="text-align: center;"><b><u>KICK BUCKET.</u></b></p> <ul data-bbox="199 589 1007 674" style="list-style-type: none"><li>- Mobile resist four foot design made of 18/10 CrNi steel.</li><li>- Four plastic swivel castors, wear-resistant, electrically conductive.</li><li>- Diameter Pan: 450 mm, Height: 380 mm, Weight: 5 kg.</li></ul>	<b>10</b>

**ELECTROSURGICAL CAUTARY MACHINE WITH CART.****ITEM NO: 18**

Specification For: <b>ELECTROSURGICAL CAUTARY MACHINE WITH CART</b>	<b>QTY</b>
<p style="text-align: center;"><b><u>ELECTROSURGICAL CAUTARY MACHINE WITH CART.</u></b></p> <ul style="list-style-type: none"> <li>- High frequency electro surgical unit with automatic output control using the latest microprocessor technology, cut and coagulation tool in monopolar and bipolar applications.</li> <li>- Auto cut mode: Monopolar, with automatic voltage control and maximum H.F rated output power of 200 Watts.</li> <li>- Endo cut mode: Manopolar, support of initial incision and cutting PPS, PowerPeak System. The H.F rated output power is 200 Watts at 500 ohms.</li> <li>- Coagulation Channel: H.F Power adjustment: with up/down increment key.</li> <li>- Soft Coagulation, Monopolar: From of HF current: Sine-shaped, Nominal frequency of HF voltage: 330 kHz, Nominal HF output: 120 Watts at 125 ohms.</li> <li>- Forced Coagulation, Monopolar: From of HF current: Pulse-modulated, Nominal frequency of HF voltage: 1 MHz, Nominal HF output: 120 watts at 350 ohms.</li> <li>- Bipolar Coagulation Mode: From of HF current: Sine-shaped, Nominal frequency of HF current: 330 kHz, Nominal HF output: 120 watts at 125 ohms. Start of coagulation: By foot pedal or Auto Start.</li> <li>- Dimension: W x H x D 280 x 152 x 368 mm, Weight: 8 kg</li> <li>- Voltage: <b>110V- 220V 60 Hz</b></li> </ul>	<b>1</b>

**STEAM STERILIZER ECOSTE 101 SINGLE DOOR WITH ALL ACCESS****ITEM NO: 19**

Specification For: <b>STEAM STERILIZER ECOSTE 101 SINGLE DOOR WITH ALL ACCESS.</b>	<b>QTY</b>
<p data-bbox="220 555 1257 589"><b><u>STEAM STERILIZER ECOSTE 101 SINGLE DOOR WITH ALL ACCESS</u></b></p> <ul style="list-style-type: none"> <li data-bbox="199 622 564 651">- Chamber volume 314 liters.</li> <li data-bbox="199 651 1023 680">- External Dimension including base: H x W x D 1981x1300x970 mm</li> <li data-bbox="199 680 963 710">- Internal Dimensions of chamber: H x W x D 700x650x690 mm</li> <li data-bbox="199 710 1158 739">- Double-processor control (Master Slave) to guarantee efficiency of sterilization.</li> <li data-bbox="199 739 528 768">- Built in steam generator.</li> <li data-bbox="199 768 879 797">- Construction in S/Steel, Working pressure: 5, to 10 bar</li> <li data-bbox="199 797 735 826">- Single opening with 1 vertical sliding door.</li> <li data-bbox="199 826 1251 891">- Automatic operation through microprocessor controller with 6 available cycles: * instruments/glassware, * textile, * rubber good, * vacuum test, * Bowie &amp; Dick, * liquids.</li> <li data-bbox="199 891 778 920">- Automatic control of temperature with PT 100.</li> <li data-bbox="199 920 1235 985">- 2 timers for control of sterilization and drying times, 2 way linear recorder for pressure and temperature in chamber.</li> <li data-bbox="199 985 900 1014">- Loading Cart universal two each made of stainless steel.</li> <li data-bbox="199 1014 671 1043">- Voltage: <b>220V-380V 60 Hz 3 phase.</b></li> </ul>	<b>1</b>

**OR CELING LIGHT BLUE 90 SINGLE SATELLITE WITH ALL ACCESS**

**ITEM NO: 20**

Specification For: <b>OR CELING LIGHT BLUE 90 SINGLE SATELLITE WITH ALL ACCESS</b>	<b>QTY</b>
<b><u>OR CELING LIGHT BLUE 90 SINGLE SATELLITE WITH ALL ACCESS</u></b>	<b>5</b>

**ERBOTOM ICC 200 ENDO- CUT WITH CART**

**ITEM NO: 21**

Specification For: <b>ERBOTOM ICC 200 ENDO- CUT WITH CART</b>	<b>QTY</b>
<b><u>ERBOTOM ICC 200 ENDO- CUT WITH CART</u></b>	<b>6</b>

**INSTRUMENT TROLLEY**

**ITEM NO: 22**

Specification For: <b>INSTRUMENT TROLLEY</b>	<b>QTY</b>
<b><u>INSTRUMENT TROLLEY</u></b>	<b>3</b>

**SEPTIC FLUID SCUTION PUMP WITH TROLLEY**

**ITEM NO: 23**

Specification For: <b>SEPTIC FLUID SCUTION PUMP WITH TROLLEY</b>	<b>QTY</b>
<b><u>SEPTIC FLUID SCUTION PUMP WITH TROLLEY</u></b>	<b>1</b>