

	Bait Al Batterjee Medical Trading Co.
	Saudi German Hospital Group
	Al Zahra Dist. Jeddah
	Tel. No. 02 – 6620 296 / 6620 396 / 6620 279 Ext: 5029
	Fax No. 02 – 256 2973
	Direct Line 02 - 6905129

Date : 15 / 09 / 2008	Contact Person : Dr. Alaa El Shreef - Dr. Mohy khalil
Pages : 1 : 45	E mail Address : xray1.jed@sghgroup.net - bab@sghgroup.net
Vender :	Mobile : 00966 505 640 079 - 00966 561 052 512
Attention : Sales Manager	
Enclosed please find our Tender Document for <u>O.R DEPARTMENT</u>	
Please submit your best prices for the following items complete specification, Catalogue copy & C.V for units	
Your offer in witting should reach to the undersign before 15 / Dec / 2008	
You may quote your equivalent product if you are unable to offer the specification item	

General Requirements for the Negotiable Tender

- 1- The Manufacture has to offer the Highest & Latest model in the required Item with all the Encouraging specification which let the dean of the tender to choose the Product.
- 2- The offer must contain all Hardware & Software available At time of tender.
- 3- The Manufacture will apply all the Upgrade will be added to the unit Free of Charge.
- 4- The Manufacture will offer clear C.V of the Same Model in his quotation with year of production.
- 5- Warrantee is (5) years including labor & Spare parts & Accessories needed for the perfect work of the unit.
- 6- The Manufacture will assure the wok of the unit during the Warrantee with Minimum of 320 days / Year.
- 7- It will be Service Contract for (5) years after the warrantee period in the offer of the manufacturer.
- 8- It's better for the Manufacturer to offer Basic Unit & alternative for each item.
- 9- It's well known that The Company which will win the Tender is going to Sign the Contract with SGH Group.
- 10- This Contract Details will be Discusses with the Company after The Evaluation with the whole Higher Management SGH Group.
- 11- The specification in the book is the nearly accepted but not restricted so each Company Can offer the best Models which Help doctors & Staff to Offer the Best Benefits for the Patient.

Dr. MOHY KHALIL
bab@sghgroup.net

INDEX

DEPARTMENT: OR

S.No	Items Descriptions	Qty	No. of pages	Manufacture	Origin	Model	Unit Price	Total Price
1	OR CELING LIGHT BLUE 130 WITH 3 DOM WITH CAMERA PROVISION WITH ALL ACCESS.	4	1					
2	PENDANT CELING DOUBLE ARM DUO BETA 800 SPRING ARMS ONE FULL MOVABLE SPRING ARM FOR SURGERY AND ONE FOR ANAESTHESIA SIDE WITH ALL ACCESS.	4	1					
3	SCRUB SINK FOR 4 PERSON KNEE OPERATING.	4	1					
4	DISPENSER SYSTEM F/NAIL BURSHES MADE OF CHROME- NECKEL STEEL, FIXING ON THE WALL	10	1					
5	X-RAY VIEWER 80 × 43 CM	4	1					
6	ALPHAMAQUET OPERATING TABLE W/R TRANSMITTER AND CHARGING UNIT WITH ALL ACCESS.	4	1					
7	MODULAR UNIVERSAL TABLE TOP	5	1					
8	TRANSPORTER FOR TABLE TOP	6	1					
9	EXTENSION TABLE TOP FOR ORTHOPAEDICS AND TRAUMATOLOGY WASHABLE WITH HEAD REST, LEG PLATES	1	1					
10	MOBIL PLASTER & EXTENSION TABLE WITH HYDRAULIC AND HIGH ADJUSTMENT.	1	1					
11	ERBOTOM ICC 350 ENDO- CUT WITH CART AND ALL ACCESS	5	1					
12	MAYO INSTRUMENT TABLE.	5	1					
13	INSTRUMENT TABLE.	20	1					
14	FOOT STEP DOUBLE	8	1					
15	FOOT STEP SINGLE	8	1					
16	BOWL STAND WITH HEATER	6	1					
17	KICK BUCKET	10	1					
18	SWISS LITHOCLAST INTRACOPREAL LITHOTRIPTER WITJ ACCESS.	1	1					
19	RECTUMIRRIGATION UNIT WITH COMPLETE ACCESSORIES.	1	1					
20	DISINFECTION MACHINE PARATERMINAL F 95	2	1					
21	CO2 LSER WITH MICROMANIPULATOR	1	1					
22	HOLMIUM Nd YAG LASER FOR UROLOGY	1	1					
23	SOVEREIGN PHACOEMULSIFICATION WITH COMPLETE ACCESS. ALLERGAN FOR OPHTHALMOGY	1	1					
24	SURGICAL MICROSCOPE WITH ERBIUM YAG LASER MOBIL FLOOR STAND WITH MOTORIZED ZOOM FOR ENT.	1	1					
25	SURGICAL MICROSCOPE WITH MOTORIZED ZOOM, XY-COUPLING MOBIL FLOOR STAND FOR OPHTHALMOLOGY.	1	1					
26	SURGICAL MICROSCOPE WITH MOTORIZED ZOOM FOR NEURO AND P & R SURGERY.	1	1					
27	SONY 20" COLOR MONITOR.	1	1					
28	PLASTER CUTTER SAW	4	1					
29	HANAULUX 1001 STANDARD RAIL VERSION WITH TRANSFORMER AND FOLLOWING ITEMS	1 IOT	1					
30	COMPLETE INSTRUMENTS SETS FOR ALL HOSPITAL	1 IOT	1					
31	COMPLETE INSTRUMENTS SETS FOR OPHTHALMOLOGY	1 IOT	1					

INDEX

DEPARTMENT: OPERATING ROOM

S.No	Items Descriptions	Qty	No. of pages	Manufacture	Origin	Model	Unit Price	Total Price
32	HEUI ARTHROPLASTY KNEE	1	1					
33	TOTAL KNEE REPLACEMENT	1	1					
34	PRIMARY TOTAL KNEE	1	1					
35	TOTAL HIP REPLACEMENT	1	1					
36	SPINE	1	1					
37	H.B.S SYSTEM	1	1					
38	CANNULATTED SCREW 6.5 SYSTEM	1	1					
39	CANNULATTED SCREW 4.0 SYSTEM	1	1					
40	CANNULATTED SCREW 3.5 SYSTEM	1	1					
41	CANNULATTED SCREW 2.7 SYSTEM	1	1					
42	SHOULDER INSTRUMENTATION SYSTEM	1	1					

**OR CELING LIGHT BLUE 130 WITH 3 DOM WITH CAMERA PROVISION
WITH ALL ACCESS.**

ITEM NO: 1

Specification For: <u>OR CELING LIGHT BLUE 130 WITH 3 DOM WITH CAMERA PROVISION WITH ALL ACCESS.</u>	QTY
<p align="center"><u>OR CELING LIGHT BLUE 130 WITH 3 DOM WITH CAMERA PROVISION WITH ALL ACCESS.</u></p> <ul style="list-style-type: none"> - Illumination 120,000 Lux x 100,000 Lux - Diameter of satellite excluding handles: 900 mm x 510 mm - Number of prisms: 4 355 x 2 184 - Diameter of large field: 28 cm x 17 cm - Diameter of small field: 20 cm x 14 cm - Depth of the volume of light: 80 cm x 80 cm - Color rendering index (IRC): 95 +/- 2 Ra x 95 +/- 2 Ra - Color Temperature: 3300 K (+/- 200) x 3300 - Infrared filtratin: Absorbent + dichroic x absorbent Athermal filters - Radiant energy: 4.5 x 5.5 mW/m².Lux - Input power: 375 x 125 VA - Low voltage consumption: 12 x 4 A - Voltage at bulb terminals: 23V x 23 V - Number of halogen bulbs 24V/100 W: 3 x 1 - Minimum height of room for clearance of 2880 mm - Positioning range of satellite: 12280 mm - Maximum reaction torque of configuration: 141 m.DaN - Voltage: 110V- 220V 60 Hz 	4

**PENDANT CELING DOUBLE ARM DUO BETA 800 SPRING ARMS ONE FULL
MOVABLE SPRING ARM FOR SURGERY AND ONE FOR ANAESTHESIA
SIDE WITH ALL ACCESS**

ITEM NO: 2

Specification For PENDANT CELING DOUBLE ARM DUO BETA 800 SPRING ARMS ONE FULL MOVABLE SPRING ARM FOR SURGERY AND ONE FOR ANAESTHESIA SIDE WITH ALL ACCESS	QTY
<p align="center"><u>PENDANT CELING DOUBLE ARM DUO BETA 800 SPRING ARMS ONE FULL MOVABLE SPRING ARM FOR SURGERY AND ONE FOR ANAESTHESIA SIDE WITH ALL ACCESS</u></p> <ul style="list-style-type: none"> - Parking and working position are fundamentally different - Speedier change-over of medial equipment and instruments - Quick, easy swiveling in case of emergency - Supply of high and low tension current as well as medical gases to the surgical instruments. - Clearance height of 2 m - Modular equipping of appliances of differing weights and sizes - Variable work positions when patients are brought in and out of anesthesia areas. - The basic components consist of: Box, Shelves, Drawers, Keyboard/writing drawers, Tilt/Swivel section, I.V Poles, docking/lifting system for apparatus, Electrical connections, Medical gas connection, special apparatus, communication and data lines. - Air motor - Voltage: 110V- 220V 60 Hz 	4

SCRUB UP SINK FOR 4 PERSON KNEE OPERATING.**ITEM NO: 3**

Specification For: SCRUB UP SINK FOR 4 PERSON KNEE OPERATING.	QTY
<p style="text-align: center;"><u>SCRUB UP SINK FOR 4 PERSON KNEE OPERATING.</u></p> <ul style="list-style-type: none"> - Scrub up unit chrome nickel steel 18/10, drainage channel uninterrupted each with gradient to the drainage, Drainage set with sieve valve and complete drainage pipe work to a central point. Back wall 110 mm deep, constructed as installation panel, completely with supply pipe work and installation for operating fittings. Sloping front bottom with extensive removable revision covers, protected by box spanner lock-mechanism. - Including 2 built-in thermostat, 4 outlet arm and 4 built-in hip operated valve - Dimension: W x D x H 3500mm x 540mm x 1000mm - Voltage: 110V- 220V 60 Hz 	4

**DISPENSER SYSTEM F/NAIL BURSHES MADE OF CHROME- NECKEL
STEEL, FIXING ON THE WALL**

ITEM NO: 4

Specification For: DISPENSER SYSTEM F/NAIL BURSHES MADE OF CHROME- NECKEL STEEL, FIXING ON THE WALL	QTY
<p style="text-align: center;"><u>DISPENSER SYSTEM F/NAIL BURSHES MADE OF CHROME- NECKEL STEEL, FIXING ON THE WALL</u></p> <p>- Dispenser for 20 brushes with suspension hook Size: 260x300x65 mm</p>	10

X-RAY VIEWER 80×43 CM**ITEM NO: 5**

Specification For: X-RAY VIEWER80×43 CM	QTY
<p data-bbox="523 658 906 694" style="text-align: center;"><u>X-RAY VIEWER80×43 CM</u></p> <ul data-bbox="199 757 1225 936" style="list-style-type: none">- To built-in wall with surrounding frame to cover the joint, Viewing area with 3 daylight fluorescent tubes of 30 Watts each, with electronic stepless brightness control- Max. Luminous density : 2400 – 3600 cd/sq m- Dimension: 1000 x 625 x 102 mm W x H x D- Power input in Watt: 110, Current in ampere: 1.1- Voltage: 110V- 220V 60 Hz	4

ALPHAMAQUET OPERATING TABLE W/R TRANSMITTER AND CHARGING UNIT WITH ALL ACCESS.

ITEM NO: 6

Specification For: ALPHAMAQUET OPERATING TABLE W/R TRANSMITTER AND CHARGING UNIT WITH ALL ACCESS.	QTY
<p align="center"><u>ALPHAMAQUET OPERATING TABLE W/R TRANSMITTER AND CHARGING UNIT WITH ALL ACCESS.</u></p> <ul style="list-style-type: none"> - The column movement –490 mm of vertical stroke, +/- 40° of trendelenburg/reverse trendelenburg adjustment, +/- 27° of lateral tilt. The control electronics feature automatic return to the 0-position. - On a flat base, The transporter can lift, move and set down the column and table top at any desired location, special design, maintenance free batteries and electronic charge control are integrated into the base. - Electromechanical, battery powered, movable with transporter, including IR transmitter mobile charging unit. - Voltage: 110V-220V 60 Hz 	4

MODULAR UNIVERSAL TABLE TOP:**ITEM NO: 7**

Specification For: MODULAR UNIVERSAL TABLE TOP:	QTY
<p style="text-align: center;"><u>MODULAR UNIVERSAL TABLE TOP:</u></p> <ul style="list-style-type: none"> - Maximum of 6 subdivisions- head plate, upper back, lower back, seat plate and split let plates. Motor-powered table top adjustments providing 275 mm of longitudinal shift, lower back up/down, leg plates up/down, either simultaneously or individually. Manual adjustment to raise/lower back plate and 60 mm of longitudinal extension. - With external table top control, PUR padded, with Standard back plate for general surgery, PUR padded, Head rest with double articulation tilt able with cassette rails, PUR padded, Leg plates (coded) with double-joint abduction, PUR padded. 	5

TRANSPORTER FOR TABLE TOP:**ITEM NO: 8**

Specification For: TRANSPORTER FOR TABLE TOP:	QTY
<p data-bbox="485 658 991 696" style="text-align: center;"><u>TRANSPORTER FOR TABLE TOP:</u></p> <ul data-bbox="199 723 1254 842" style="list-style-type: none"><li data-bbox="199 723 1254 842">- Made from CrNi steel and an aluminum alloy, can be moved longitudinally and laterally with four tandem swivel castor, two of which can be locked centrally at the left and right front castors can also be fixed individually. Additional stabilization castor at the side for straight-line travel.	6

EXTENSION TABLE TOP FOR ORTHOPAEDICS AND TRAUMATOLOGY
WASHABLE WITH HEAD REST, LEG PLATES.

ITEM NO: 9

Specification For: EXTENSION TABLE TOP FOR ORTHOPAEDICS AND TRAUMATOLOGY WASHABLE WITH HEAD REST, LEG PLATES.	QTY
<p><u>EXTENSION TABLE TOP FOR ORTHOPAEDICS AND TRAUMATOLOGY</u> <u>WASHABLE WITH HEAD REST, LEG PLATES.</u></p> <ul style="list-style-type: none"> - Maximum of 7 subdivisions- head plate-detachable tilting back plate can be raised and lowered by about 90o/60o, Seat plate with two triangular buttocks supports at the side, Leg plates, pair detachable PUR padded. - Including following basic accessories - 2x Telesopic traction bar(short and long) - 2x Elongation bars - 1x Screw tension device - 1x Foot plate support - 1x Rotation and tilting clamp - 1x Traction stirrup clamp with rotation - 1xCountertraction post for neck of femur w/pad - 1x side rail elongation. 	1

MOBIL PLASTER & EXTENSION TABLE WITH HYDRAULIC AND HIGH ADJUSTMENT

ITEM NO: 10

Specification For: MOBIL PLASTER & EXTENSION TABLE WITH HYDRAULIC AND HIGH ADJUSTMENT	QTY
<p><u>MOBIL PLASTER & EXTENSION TABLE WITH HYDRAULIC AND HIGH ADJUSTMENT</u></p> <ul style="list-style-type: none"> - Table, Plaster/Extension, Mobile, Radio translucent top including PU-Foam pads with following accessories: - 1x Head rest - 1x pair of divided/removable leg plates - 2x Telescopic traction bars - 2x Leg plate supports - 1x Side rail elongation - Height adjustment of table top via hydraulically operated foot lever from 745 to 1110 mm - Trendelenburg position 15° - 6 easy-running ball bearing castors, electrically conductive, lockable - Lower traction bars extendable in longitudinal direction. Equipped with vertical telescopic bar for fitting let plate supports, Screw tension devices or gallows - Table top divided into following section: - Head plate, adjustable and removable - Back plate manually adjustable - Seat plate equipped with 2 buttock supports, Leg plates/divided and removable - Cassette insertion from head-end to the hip area - Lateral insertion of of cassette from left or right hand side in hip area - Cassette size 24x30 cm - Unimpeded application of image intensifier - Table top frame bars and accessories made of chrome nickel steel 18/10 - Hydraulic unit, enameled, knock-proof and resistant to disinfectants. 	<p>1</p>

ERBOTOM ICC 350 ENDO- CUT WITH CART AND ALL ACCESS**ITEM NO: 11**

Specification For: ERBOTOM ICC 350 ENDO- CUT WITH CART AND ALL ACCESS	QTY
<p><u>ERBOTOM ICC 350 ENDO- CUT WITH CART AND ALL ACCESS</u></p> <ul style="list-style-type: none"> - High frequency electro surgical unit with automatic output control using the latest microprocessor technology, cut and coagulation tool in monopolar and bipolar applications. - Auto cut mode: Monopolar, with automatic voltage control and maximum H.F rated output power of 350 Watts. - Endo cut mode: Manopolar, support of initial incision and cutting PPS, PowerPeak System. The H.F rated output power is 300 Watts at 500 ohms. - Coagulation Channel: H.F Power adjustment: with up/down increment key. - Soft Coagulation, Monopolar: From of HF current: Sine-shaped, Nominal frequency of HF voltage: 350 kHz, Nominal HF output: 120 Watts at 500 ohms. - Forced Coagulation, Monopolar: From of HF current: Pulse-modulated, Nominal frequency of HF voltage: 1 MHz, Nominal HF output: 120 watts at 500 ohms. - Bipolar Coagulation Mode: From of HF current: Sine-shaped, Nominal frequency of HF current: 350 kHz, Nominal HF output: 120 watts at 125 ohms. Start of coagulation: By foot pedal or Auto Start. - Dimension: W x H x D 410 x 152 x 368 mm, Weight: 10 kg - Voltage: 110V- 220V 60 Hz 	5

MAYO INSTRUMENT TABLE.**ITEM NO: 12**

Specification For: MAYO INSTRUMENT TABLE.	QTY
<p data-bbox="491 667 938 698" style="text-align: center;"><u>MAYO INSTRUMENT TABLE.</u></p> <ul data-bbox="199 728 1257 846" style="list-style-type: none">- Integral precision hydraulic pump. Base and lift column made of 18/10 CrNi steel.- Height adjustable via pump pedal coated with electrically conductive rubber compound.- Plate dimension: Length: 700 mm, Width: 500 mm Height adjustable: 900-1350 mm- Weight: 38 kg.	5

INSTRUMENT TABLE.**ITEM NO: 13**

Specification For: INSTRUMENT TABLE.	QTY
<p data-bbox="549 629 884 663" style="text-align: center;"><u>INSTRUMENT TABLE.</u></p> <ul data-bbox="199 689 1166 808" style="list-style-type: none">- Mobile 4-leg frame construction made of 18/10 CrNi steel with 2 plates.- 4- plastic swivel castors, wear-resistant, non-discoloring, electrically conductive.- Length: 950 mm, Width: 635 mm, Height: 900 mm- Weight: 18.5 kg.	20

FOOT STEP DOUBLE.**ITEM NO: 14**

Specification For: FOOT STEP DOUBLE.	QTY
<p data-bbox="555 629 877 663" style="text-align: center;"><u>FOOT STEP DOUBLE.</u></p> <ul data-bbox="199 689 869 842" style="list-style-type: none">- Stable four-leg design, made of 18/10 steel- Tread is ribbed and slip-resistant.- Electrically conductive rubber feet.- Length: 600 mm, Width: 650 mm Height: 220/440 mm- Weight: 14kg.	8

FOOT STEP SINGLE.**ITEM NO: 15**

Specification For: FOOT STEP SINGLE.	QTY
<p data-bbox="560 622 871 656" style="text-align: center;"><u>FOOT STEP SINGLE.</u></p> <ul data-bbox="199 685 820 835" style="list-style-type: none">- Stable four-leg design, made of 18/10 steel- Tread is ribbed and slip-resistant.- Electrically conductive rubber feet.- Length: 600 mm, Width: 350 mm Height: 130 mm- Weight: 7 kg.	8

BOWL STAND WITH HEATER.**ITEM NO: 16**

Specification For: BOWL STAND WITH HEATER.	QTY
<p style="text-align: center;"><u>BOWL STAND WITH HEATER.</u></p> <ul style="list-style-type: none">- Mobile, five-leg resist design made of 18/10 CrNi steel.- Painted cast housing with heating element and integral safety thermostat limiting temperature to 60°C.- Five plastic swivel castors, wear-resistant, non-discolouring when in contact with other material, Electrically conductive, 75 mm diam. With lint and thread shield, two castors with locking brakes.- Diameter: 400 mm, Height adjustment: 920-1290 mm- Weight: 12.5 kg.- Voltage: 110V-220V 60 Hz	6

KICK BUCKET.**ITEM NO: 17**

Specification For: KICK BUCKET.	QTY
<p data-bbox="598 622 833 656" style="text-align: center;"><u>KICK BUCKET.</u></p> <ul data-bbox="199 685 1007 775" style="list-style-type: none">- Mobile resist four foot design made of 18/10 CrNi steel.- Four plastic swivel castors, wear-resistant, electrically conductive.- Diameter Pan: 450 mm, Height: 380 mm, Weight: 5 kg.	10

SWISS LITHOCLAST INTRACOPREAL LITHOTRIPTER WITJ ACCESS**ITEM NO: 18**

Specification For: SWISS LITHOCLAST INTRACOPREAL LITHOTRIPTER WITJ ACCESS	QTY
<p><u>SWISS LITHOCLAST INTRACOPREAL LITHOTRIPTER WITJ ACCESS</u></p> <ul style="list-style-type: none"> - Including following: - - 2 standard hand pieces - Probes size, 0.8 mm, 1.0 mm, 1.6 mm and 2.0 mm each - 1 air Supply Cord - 1 electrical Connection - 2 Silicone tubes with connector - 1 spare silicone tube - 2 sterilization caps - 1 pack of seals - 2 pneumatic foot controls - 1 suitcase - Medical air compressor - Trolley - Sterilization container - Standard Lithovac master set - Suction set for kidney application - Suction set for bladder application - Suction set for ureter applications - Voltage: 110V-220V 60 Hz 	1

RECTUMIRRIGATION UNIT WITH COMPLETE ACCESSORIES.**ITEM NO: 19**

Specification For: RECTUMIRRIGATION UNIT WITH COMPLETE ACCESSORIES.	QTY
<p><u>RECTUMIRRIGATION UNIT WITH COMPLETE ACCESSORIES.</u></p> <ul style="list-style-type: none"> - Including following: - - Fixture for irrigation rack, re-usable tubing set, vacuum tube, hygienic filter and power cable 3 m long - Tube set box/10 - Tube set PVC, with safe-lock connector box/10 - Collecting container, 3 liters, including fixture, autoclavable - Fixture for irrigation rack - Side mounting - Infusion bottle holder, height adjustable - Clamping device color- ruby-red - Voltage: 110V-220V 60 Hz 	1

DISINFECTION MACHINE. PARATERMINAL F 95**ITEM NO: 20**

Specification For: DISINFECTION MACHINE. PARATERMINAL F 95	QTY
<u>DISINFECTION MACHINE. PARATERMINAL F 95</u> - Voltage: 110V-220V 60 Hz	2

CO2 LSER WITH MICROMANIPULATOR.**ITEM NO: 21**

Specification For: CO2 LSER WITH MICROMANIPULATOR.	QTY
<p style="text-align: center;"><u>CO2 LSER WITH MICROMANIPULATOR.</u></p> <ul style="list-style-type: none"> - Laser: Sealed-off, DC Excited CO2 laser - Wavelength: 10.6 microns, infrared, Mode Structure:TEM₀₀ - Power on Tissue: Continuously adjustable CW: 1-60W , Super pulse: Average: 0.5-10W, Peak: 300W - Pulsar: Average 1-25W - Flash Scanner: SurgiTocuch for char-free ablation of tissue. - Aiming Beam: 3mW red He-Ne laser, adjustable intensity control, Blocked in OFF position. - Delivery System: Lightweight, carbon fiber, 7-joint, fixed mirror, spring balanced articulated arm, - Optical Design: Mirror-based, achromatic co focal, Fully coaxial with microscope optical axis. - Working distance: Continuously variable from 200 to 400mm - Minimum spot size: 160 microns - Defocus: Continuously variable with adjustable limiter. - Joystick: 10:1 magnification, adjustable tension, autoclavable handle. - Power Transmission: >90% unlimited , power input - Voltage: 110V-220V 60 Hz 	1

HOLMIUM Nd YAG LASER FOR UROLOGY.**ITEM NO: 22**

Specification For: HOLMIUM Nd YAG LASER FOR UROLOGY.	QTY
<p data-bbox="389 696 1043 734" style="text-align: center;"><u>HOLMIUM Nd YAG LASER FOR UROLOGY.</u></p> <ul data-bbox="199 763 951 1032" style="list-style-type: none">- Configuration: 80 Watt- Laser Source: Holmium: Yag- Wavelength: 2.1 micron- Energy per pulse: 0.2-4.0 Joules- Pulse duration: Up to 500 Microseconds- Aiming Beam: 2.5 mW at 650nm, 3 intensity settings- Delivery system: Reusable, flexible fiber delivery, 23 options.- Cooling: Self-contained water-to-air exchanger- Voltage: 110V-220V 60 Hz	1

SOVEREIGN PHACOEMULSIFICATION WITH COMPLETE ACCESS.
ALLERGAN FOR OPHTHALMOGY

ITEM NO: 23

Specification For: SOVEREIGN PHACOEMULSIFICATION WITH COMPLETE ACCESS. ALLERGAN FOR OPHTHALMOGY	QTY
<p align="center"><u>SOVEREIGN PHACOEMULSIFICATION WITH COMPLETE ACCESS.</u> <u>ALLERGAN FOR OPHTHALMOGY</u></p> <ul style="list-style-type: none"> - Phaco Power: 0% to 100% in 5% increment - Phaco Vacuum Levels: 0 to 500 mm Hg in 5-mm Hg increments. - Pump Flow Rate: 10 to 40 cc per min, in 2-cc increments - IV SPECIFICATIONS - Vacuum levels: 0 to 500mm Hg - Pump Flow Rate: 10 to 40 cc per min - Maximum Travel: 30 in/76cm - Setting Range: 0 to 30 in/0 to 76 cm - Velocity: 4 in per sec/10 cm per sec - VITRECTOMY SPECIFICATION - Pneumatic Guillotine (PVIT) cutter rate:180 to 400 cuts per min (CPM) - Electronic Oscillating(EVIT) cutter rate: 100 to 600 cuts per min (CPM). - Vacuum Level: 0 to 500mm Hg in 5-mm Hg increments. - Pump Flow Rate: 10 to 40cc per min, in 2-cc increments. - Voltage: 110V-220V 60 Hz 	1

**SURGICAL MICROSCOPE WITH ERBIUM YAG LASER MOBIL FLOOR
STAND WITH MOTORIZED ZOOM FOR ENT.**

ITEM NO: 24

Specification For: <u>SURGICAL MICROSCOPE WITH ERBIUM YAG LASER MOBIL FLOOR STAND WITH MOTORIZED ZOOM FOR ENT.</u>	QTY
<p align="center"><u>SURGICAL MICROSCOPE WITH ERBIUM YAG LASER MOBIL FLOOR STAND WITH MOTORIZED ZOOM FOR ENT.</u></p> <ul style="list-style-type: none"> - Magnification: - Motorized zoom: 1:6 ratio, adjustable via handgrips or foot control panel - Focus system: Internal, motorized, continuously variable, adjustable via handgrips or foot control panel - Working Range: 200-415 mm - Main Binocular Tube: Inclined 0-180o with 12.5x or 10x wide-angle eyepieces - Automatic Circuit Breaker - Weight: 165 kg - Voltage: 110V-220V 60 Hz 	1

SURGICAL MICROSCOPE WITH MOTORIZED ZOOM, XY-COUPLING
MOBIL FLOOR STAND FOR OPHTHALMOLOGY.

ITEM NO: 25

Specification For: SURGICAL MICROSCOPE WITH MOTORIZED ZOOM, XY-COUPLING MOBIL FLOOR STAND FOR OPHTHALMOLOGY.	QTY
<p align="center"><u>SURGICAL MICROSCOPE WITH MOTORIZED ZOOM, XY-COUPLING</u> <u>MOBIL FLOOR STAND FOR OPHTHALMOLOGY.</u></p> <ul style="list-style-type: none"> - Microscope: - Apochromatic optics, Motorized zoom system, zoom ratio 1:6 - Focusing range: 50 mm rest at the press of a button - 180° tilt able tube, 45° inclined tube, 12.5x eyepieces, objective lens f=200 mm - Magnification with 12.5x eyepieces 4.4x-26.3x - Field of view diameter 8.4 mm-50.3 mm - Fiber light guide, Halogen lamp bulb 12V, 100W, Filter against UV exposure - Protection against IR exposure, 6° illumination with continuous fading mechanism - XY coupling: adjustment range 40x40 mm, Control for reset of XY coupling, focus - Inversion of the XY direction of travel possible via foot control - Voltage: 110V-220V 60 Hz 	1

**SURGICAL MICROSCOPE WITH MOTORIZED ZOOM FOR NEURO AND P
& R SURGERY.**

ITEM NO: 26

Specification For: SURGICAL MICROSCOPE WITH MOTORIZED ZOOM FOR NEURO AND P & R SURGERY.	QTY
<p><u>SURGICAL MICROSCOPE WITH MOTORIZED ZOOM FOR NEURO AND P & R SURGERY.</u></p> <ul style="list-style-type: none"> - Focal length/working distance: 200 to 412 mm - Binocular tube/eyepieces: 180° widefield tiltable tube with high eyepoint widefield eyepieces 10, 12.5x - Magnification: 1.5x to 18.2x - Illuminated field diameter: Full field of view down to approach 13 mm, spot diameter continuously adjustable - Integrated 180W xenon illumination with backup xenon lamp in the fast action - Optimum ergonomic convenience in the face-to-face configuration with the new stereo bridge, rotatable dovetail - Fast and exact setting of the focus and XYU position; speeds of travel dependent on magnification selected - Maximum arm extension of suspension system: 1300 mm - Voltage: 110V-220V 60 Hz 	1

SONY 20" COLOR MONITOR

ITEM NO: 27

Specification For: SONY 20" COLOR MONITOR	QTY
<p style="text-align: center;"><u>SONY 20" COLOR MONITOR</u></p> <p>- Voltage: 110V-220V 60 Hz</p>	1

PLASTER CUTTER SAW.**ITEM NO: 28**

Specification For: PLASTER CUTTER SAW.	QTY
<p style="text-align: center;"><u>PLASTER CUTTER SAW.</u></p> <ul style="list-style-type: none">- Capacity: 125W, 15,000 Oscillation- Weight: 1.5 Kg including 2 Saw Blades 50mm, and 65 mm diameter- Voltage: 110V-220V 60 Hz	4

HANAULUX 1001 STANDARD RAIL VERSION WITH TRANSFORMER AND FOLLOWING ITEMS:-

ITEM NO: 29

Specification For: <u>HANAULUX 1001 STANDARD RAIL VERSION WITH TRANSFORMER AND FOLLOWING ITEMS:-</u>	QTY
<p align="center"><u>HANAULUX 1001 STANDARD RAIL VERSION WITH TRANSFORMER AND FOLLOWING ITEMS:-</u></p> <ul style="list-style-type: none"> - Suction Unit Air #Z096210120 - Air Probe 6 mm DIN comr. #Z051010123 - Basket for rail mounting + connects to the carrying frame, 25x10 mm #AG029501 - Basket 170x130x85 #Z851300100 - Emergency Oxygen Unit #57507539 - O2 Cylinder 3.0 L #T090110301 - Flow meter O2 15 DIN #Z010510213 - Multi-outlet 2xO2, 2xAir DIN #Z801412033 - Multi-outlet 2xO2+ 2xN2O DIN #Z801413033 - Hose Connector #AN011400 - Gas Probe O2 DIN #Z051010113 - Air Probe 6 mm DIN comr. #Z051010123 - Probe N2O 6mm #051010133 - Vacuum Probe 9mm DIN #Z051010143 - Inhalation Mask #Z004000200 - Adaptor #VE036303 - Suction Unit Mobile Air DIN #Z088513023 - Septic Fluid Plastic Jar #PE021401 - Flow meter D O2 15 DIN #Z020510213 - Intensive Humidifier #Z073010200 - Bubble Humidifier #Z072010100 - Flow meter O2 15 DIN 3m #Z810513213 - Bubble Humidifier #Z072010100 - Intensive Humidifier #Z073010200 - Vacuum Contraire (Direct) #Z087410143 - Septic Fluid Suction Pump #P70501001 - Suction Unit with Controller Rail mounted Vacuum #Z0297210140 - Vacuum Probe 9 mm DIN #Z051010143 - Mounting bracket connect to the carrying frame for rail mounting #AG029501 - Septic Fluid Glass Jar 5.0 L #PE008105 - Flow meter Air 15 DIN #Z010510223 - Suction Unit Mobil VAC DIN #Z088513043 	1 IOT

COMPLETE INSTRUMENTS SETS FOR ALL HOSPITAL

ITEM NO: 30

Specification For: COMPLETE INSTRUMENTS SETS FOR ALL HOSPITAL	QTY
<u>COMPLETE INSTRUMENTS SETS FOR ALL HOSPITAL</u>	1 IOT

COMPLETE INSTRUMENTS SETS FOR OPHTHALMOLOGY

ITEM NO: 31

Specification For: COMPLETE INSTRUMENTS SETS FOR OPHTHALMOLOGY	QTY
<u>COMPLETE INSTRUMENTS SETS FOR OPHTHALMOGY</u>	1 IOT

HEUI ARTHOPLASTY KNEE

ITEM NO: 32

Specification For: HEUI ARTHOPLASTY KNEE	QTY
<u>HEUI ARTHOPLASTY KNEE</u>	1

TOTAL KNEE REPLACEMENT

ITEM NO: 33

Specification For: TOTAL KNEE REPLACEMENT	QTY
<u>TOTAL KNEE REPLACEMENT</u>	1

PRIMARY TOTAL KNEE

ITEM NO: 34

Specification For: PRIMARY TOTAL KNEE	QTY
<u>PRIMARY TOTAL KNEE</u>	1

TOTAL HIP REPLACEMENT**ITEM NO: 35**

Specification For: TOTAL HIP REPLACEMENT	QTY
<p data-bbox="501 577 928 613" style="text-align: center;"><u>TOTAL HIP REPLACEMENT</u></p> <ul data-bbox="199 689 707 864" style="list-style-type: none">- accelratour ring- Total hip counted- Total hip counted .- Complete allocation Instruments set.- Complete Revision Instruments Set	1

SPINE**ITEM NO: 36**

Specification For: SPINE	QTY
<p data-bbox="667 546 762 582" style="text-align: center;"><u>SPINE</u></p> <ul data-bbox="199 618 646 831" style="list-style-type: none">- V.S.P- Isola System .- Carbon cags for .Spine Fusion .- Plifbraaeh Instruments Set .- Spine Shaves , Spreders .- Spine Antenion system	1

H.B.S SYSTEM

ITEM NO: 37

Specification For: H.B.S SYSTEM	QTY
<u>H.B.S SYSTEM</u>	1

CANNULATTED SCREW 6.5 SYSTEM

ITEM NO: 38

Specification For: CANNULATTED SCREW 6.5 SYSTEM	QTY
<u>CANNULATTED SCREW 6.5 SYSTEM</u>	1

CANNULATTED SCREW 4.0 SYSTEM

ITEM NO: 39

Specification For: CANNULATTED SCREW 4.0 SYSTEM	QTY
<u>CANNULATTED SCREW 4.0 SYSTEM</u>	1

CANNULATTED SCREW 3.5 SYSTEM

ITEM NO: 40

Specification For: CANNULATTED SCREW 3.5 SYSTEM	QTY
<u>CANNULATTED SCREW 3.5 SYSTEM</u>	1

CANNULATED SCREW 2.7 SYSTEM

ITEM NO: 41

Specification For: CANNULATED SCREW 2.7 SYSTEM	QTY
<u>CANNULATED SCREW 2.7 SYSTEM</u>	1

SHOULDER INSTRUMENTATION SYSTEM**ITEM NO: 42**

Specification For: SHOULDER INSTRUMENTATION SYSTEM	QTY
<u>SHOULDER INSTRUMENTATION SYSTEM</u> - Super Revo System & implouts . - Uini Revo System & Implouts .	1