

	Bait Al Batterjee Medical Trading Co.
	Saudi German Hospital Group
	Al Zahra Dist. Jeddah
	Tel. No. 02 – 6620 296 / 6620 396 / 6620 279 Ext: 5029
	Fax No. 02 – 256 2973
	Direct Line 02 - 6905129

Date : 15 / 09 / 2008	Contact Person : Dr. Alaa El Shreef - Dr. Mohy khalil
Pages : 1 : 42	E mail Address : xrav1.ied@sghgroup.net - bab@sghgroup.net
Vender :	Mobile : 00966 505 640 079 - 00966 561 052 512
Attention : Sales Manager	
Enclosed please find our Tender Document for PHYSIOTHERAPY DEPARTMENT	
Please submit your best prices for the following items complete specification, Catalogue copy & C.V for units	
Your offer in witting should reach to the undersign before 15 / Dec/ 2008	
You may quote your equivalent product if you are unable to offer the specification item	

General Requirements for the Negotiable Tender

- 1- The Manufacture has to offer the Highest & Latest model in the required Item with all the Encouraging specification which let the dean of the tender to choose the Product.
- 2- The offer must contain all Hardware & Software available At time of tender.
- 3- The Manufacture will apply all the Upgrade will be added to the unit Free of Charge.
- 4- The Manufacture will offer clear C.V of the Same Model in his quotation with year of production.
- 5- Warrantee is (5) years including labor & Spare parts & Accessories needed for the perfect work of the unit.
- 6- The Manufacture will assure the wok of the unit during the Warrantee with Minimum of 320 days / Year.
- 7- It will be Service Contract for (5) years after the warrantee period in the offer of the manufacturer.
- 8- It's better for the Manufacturer to offer Basic Unit & alternative for each item.
- 9- It's well known that The Company which will win the Tender is going to Sign the Contract with SGH Group.
- 10- This Contract Details will be Discusses with the Company after The Evaluation with the whole Higher Management SGH Group.
- 11- The specification in the book is the nearly accepted but not restricted so each Company Can offer the best Models which Help doctors & Staff to Offer the Best Benefits for the Patient.

Dr. MOHY KHALIL
bab@sghgroup.net

INDEX

DEPARTMENT: PHYSIOTHERAPY

S. No	ITEMS DISCRIPTION	QTY	No. of Pages	Manufacture	Origin	Model	Unit Price	Total Price
1	3D ELECTRIC MASSAGE UNIT.	1	1					
2	G-5 VIBRAMATIC MASSAGE UNIT WITH MOBILE STAND.	1	1					
3	TENS.	1	1					
4	ULTRASOUND.	1	1					
5	ELECTROTHERAPY ULTRASOUND WITH INTERFERENTIAL CURRENT UNIT.	1	1					
6	FANGO SIRRING UNIT WITH HEATING CABINET.	1	1					
7	HYDROCOLLATOR HEATING UNIT.	1	1					
8	COLPAC CHILLING UNIT.	1	1					
9	LIFTING SYSTEM (HOIST SYSTEM).	1	1					
10	OCEANDIDE 3000 (MEDICAL BATH).	1	1					
11	STEEM SAUNA UNIT	1	1					
12	SAUNA HEATER ROOM	1	1					
13	ELECTRIC LIFTER STRETCHER.	1	1					
14	FOUR CELLULAR BATH FOR ARM & FOOT.	1	1					
15	TRACTION TABLE WITH TRACTION UNIT.	1	1					
16	SALT BELT TREADMILL.	1	1					
17	AUTO EDAMA REDUCTION WITH LEG & ARM CHAMBERS.	1	1					
18	MULTIGYM HEAVY DUTY 4 STATION.	1	1					
19	CPM KNEE HIP AND ANKLE.	1	1					
20	CPM SHOULDER.	1	1					
21	CPM ELBOW.	1	1					
22	SHORTWAVE UNIT.	1	1					
23	ARTERIAL VENOUS IMPULSE SYSTEM.	1	1					
24	MEDICAL LASER 3-COMBY.	1	1					
25	ELECTRONIC TREADMILL.	1	1					
26	BIKE ERGOMETER+PULSE/WATT+PROGRAMS+POLAR.	1	1					
27	ROWING MACHINE CONTINUOUS.	1	1					
28	STEPPER HEAVY DUTY.	1	1					
29	MANUMED OPTIMAL COUCH 5 SECTION.	1	1					
30	BAR-BELL-RACK WITH CHROMIUM BAR BELLS DUMBELLS 0.5 TO 4 KG.	1	1					
31	ROLL-WEDGES-SEATS-BALL DIFFERENT SIZE.	1	1					
32	DIGFLEX SET OF 5 WITH DIFFERENT RESESTANCE.	1	1					
33	PLATFORM MOUNTED PARALLEL BAR WITH CHILD HANDRAIL ATTACHMENT AND CENTRAL DIVIDER BOARD.	1	1					
34	TRAINING STAIRS.	1	1					
35	WOODEN WALL BAR.	1	1					
36	WALL PULLEY MACHINE.	1	1					
37	SHOULDER WHEEL EXERCISE.	1	1					
38	QUADRICEPS BENCH.	1	1					
39	ORTHOPAEDIC ROLLING MIRROR.	1	1					
40	MANUMED SPECIAL TILT TABLE 2 SECTION COUCH.	1	1					

3D ELECTRIC MASSAGE UNIT.**ITEM NO: 1**

Specification For: 3D ELECTRIC MASSAGE UNIT.	QTY
<p data-bbox="480 517 948 551" style="text-align: center;"><u>3D ELECTRIC MASSAGE UNIT.</u></p> <ul data-bbox="201 580 1214 696" style="list-style-type: none">- Professional massage unit fitted with a large surface and 2 speed powerful motor- Tri-dimensional movement- 1 Rubber applicator, 1 burled rubber applicator, 1 plastic brush and 1 synthetic case- Voltage: 110V 220V 60 Hz	1

G-5 VIBRAMATIC MASSAGE UNIT WITH MOBILE STAND.

ITEM NO: 2

Specification For: G-5 VIBRAMATIC MASSAGE UNIT WITH MOBILE STAND.	QTY
<u>G-5 VIBRAMATIC MASSAGE UNIT WITH MOBILE STAND.</u> <ul style="list-style-type: none">- Speed range: 20 to 50 cycles per second- Automatic shut-off- With 6 applicators- Voltage: 110V-220V 60 Hz	1

TENS.**ITEM NO: 3**

Specification For: TENS	QTY
<p data-bbox="667 517 762 555" style="text-align: center;"><u>TENS.</u></p> <ul data-bbox="199 577 1244 761" style="list-style-type: none">- Battery-operated- Dual channel- Fully adjustable parameters including frequency pulse duration- Three modulation modes and a timer- The set consists of: Lead wire, package of self adhesive electrodes, 9 Volt battery and carrying case.	1

ULTRASOUND.**ITEM NO: 4**

Specification For: ULTRASOUND	QTY
<p data-bbox="600 510 831 546" style="text-align: center;"><u>ULTRASOUND.</u></p> <ul data-bbox="199 573 1241 752" style="list-style-type: none">- Power Consumption: 65VA- Intensity: Max. 2W/cm2 +/-20% continuous max. 3W/cm2 +/- 20%, pulsed- Frequency(at constant temperature of 25de) L probe: 0.98MHz +/-30KHz/3.09MHz +/- 50KHz, S probe: 1.02MHZ, +/-30KHz/3.11MHz+/-50kHz- Therapy Mode: 5%,10%,20%,30%,50%- Voltage: 110V-220V 60 Hz	1

ELECTROTHERAPY ULTRASOUND WITH INTERFERENTIAL CURRENT UNIT.**ITEM NO: 5**

Specification For: <u>ELECTROTHERAPY ULTRASOUND WITH INTERFERENTIAL CURRENT UNIT.</u>	QTY
<p data-bbox="172 533 1257 600"><u>ELECTROTHERAPY ULTRASOUND WITH INTERFERENTIAL CURRENT UNIT.</u></p> <ul data-bbox="199 633 1225 869" style="list-style-type: none"> - All low and medium frequency current types - Automatic vector with tetra polar interferential display - Display of the S/d-curve on screen with automatic calculation of the accommodation quotient. - Two separate channels for (a) synchronous stimulation of muscle group. - Power consumption: 25W, Intensity: Max. 50 mA into 500 ohm, Frequency: 4000 Hz, sine wave interferential frequency: 0-100 Hz - Voltage: 110V-220V 60 Hz 	1

FANGO SIRRING UNIT WITH HEATING CABINET.**ITEM NO: 6**

Specification For: FANGO SIRRING UNIT WITH HEATING CABINET.	QTY
<p data-bbox="336 546 1091 580" style="text-align: center;"><u>FANGO SIRRING UNIT WITH HEATING CABINET.</u></p> <ul data-bbox="199 611 735 757" style="list-style-type: none">- Microprocessor controlled mixer for fango,- Temperature: 50 and 80 deg.- Sterilization: 130 degree,- Dimension: 43x43x64.5 mm- Voltage: 110V-220V 60 Hz	1

HYDROCOLLATOR HEATING UNIT.**ITEM NO: 7**

Specification For: HYDROCOLLATOR HEATING UNIT.	QTY
<p data-bbox="440 510 991 546" style="text-align: center;"><u>HYDROCOLLATOR HEATING UNIT.</u></p> <ul data-bbox="199 577 1193 813" style="list-style-type: none">- High quality stainless steel- Thermostatically controlled temperature- 7.5 cm swivel-type rubber casters for silent, friction-free movement of mobile units- Easy maintenance simple to fill and drain.- CE, UL listed and cUL listed- Dimension: Lx H x W 84 x 68 x 39 cm- Including 12 standard size hot pacs- Voltage: 110V-220V 60 Hz	1

COLPAC CHILLING UNIT.**ITEM NO: 8**

Specification For: COLPAC CHILLING UNIT.	QTY
<p data-bbox="517 510 911 546" style="text-align: center;"><u>COLPAC CHILLING UNIT.</u></p> <ul data-bbox="199 577 1182 813" style="list-style-type: none">- Closed cell foam insulation for efficiency- Stainless steel, welded construction for long life- Heavy duty compressor for more efficient cooling- Specially designed interior chilling coils cool packs faster- 7.5 cm swivel-type rubber casters for silent, friction-free movement of mobile unit- Drain valve for easy cleaning and defrosting- Including 12 standard size Colpacs- Voltage: 110V-220V 60 Hz	1

LIFTING SYSTEM (HOIST SYSTEM).**ITEM NO: 9**

Specification For: LIFTING SYSTEM (HOIST SYSTEM).	QTY
<p data-bbox="443 546 986 584" style="text-align: center;"><u>LIFTING SYSTEM (HOIST SYSTEM).</u></p> <ul data-bbox="199 611 608 846" style="list-style-type: none">- Maximum load: 175 Kg- Performance: 100 lift moments- Lift distance: 2000 mm- Lift speed: 2.7 m/min- Horizontal Motor- Motor housing: Plastic ABS/PC- Accumulators: 2x12V 4 Ah- Voltage: 110V-220V 60 Hz	1

OCEANDIDE 3000 (MEDICAL BATH).**ITEM NO: 10**

Specification For: OCEANDIDE 3000 (MEDICAL BATH).	QTY
<p style="text-align: center;"><u>OCEANDIDE 3000 (MEDICAL BATH).</u></p> <ul style="list-style-type: none"> - Crutch on the bottom (Adjustable), Chromed handfull/draining plug - 6 programs (Electronic control), Emergency stop switch - Electronic control table, Electronic temperature control, Electronic bath timing set, Air/Water pulsar 42 chromed jets with pump 3000W. - Draining jet with 2 rotating jets, Air ozone 120 perforation (750W+HEAT ING 250w, 2 air programs: Intermittent or sequential - 2 air+ water programs: Relaxing 15 minutes stimulating 20 minutes - Babble pressure control, Ventral massaging +manual jet, Electronic and automatic drying system, Thermostatic mitigate, manual shower with remote control, spot light - Voltage: 110V-220V 60 Hz 	1

STEEM SAUNA UNIT.**ITEM NO: 11**

Specification For: STEEM SAUNA UNIT.	QTY
<p data-bbox="555 555 874 589" style="text-align: center;"><u>STEEM SAUNA UNIT.</u></p> <ul data-bbox="199 618 1273 797" style="list-style-type: none">- JK Exclusive cabin 213x202x207 cm, Sauna door: Polar pine or smoked glass, Sauna oven: Climate 2000 steam bath 7.5 KW- Control Unit for Climate 2000 with ventilation system- Accessories: Water Bucket, ladle Stand, hour glass, combined hydro thermometer, lamp, Oven protection, bathing rules and headrest- Voltage: 110V-220V 60 Hz	1

SAUNA HEATER ROOM.**ITEM NO: 12**

Specification For: SAUNA HEATER ROOM.	QTY
<p data-bbox="531 555 898 589" style="text-align: center;"><u>SAUNA HEATER ROOM.</u></p> <ul data-bbox="199 622 1273 801" style="list-style-type: none">- JK Exclusive cabin 213x202x207 cm, Sauna door: Polar pine or smoked glass, Sauna oven: Climate 1000-7.5 KW- Control Unit: Climate 9/6 Electronic- Accessories: Water Bucket, ladle Stand, hour glass, combined hydro thermometer, lamp, Oven protection, bathing rules and headrest- Voltage: 110V-220V 60 Hz	1

ELECTRIC LIFTER STRETCHER.**ITEM NO: 13**

Specification For: ELECTRIC LIFTER STRETCHER.	QTY
<p style="text-align: center;"><u>ELECTRIC LIFTER STRETCHER.</u></p> <ul style="list-style-type: none"> - Movable with U-frame - For usage for all stationary and nursing baths, lifting pilar made of perceive steel inside tube outside eloxatec aluminum tube, electro-mechanical lifting cylinder with ball-bearing drive, covered 24V motor with accu. - Stretcher-support height adjustable, stretcher ergonomically formed 3-folded, PVC stretcher back and foot part movable, stretcher height adjustable by hand switch including 2xsafety belt and 1 head rest - Lifting capacity: 150 kg - Height adjustment from 0-685/410-1095 mm crossable - Dimension: L x W x H 1780 x 820 x 1330 mm - Voltage: 110V-220V 60 Hz 	1

FOUR CELLULAR BATH FOR ARM & FOOT.**ITEM NO: 14**

Specification For: FOUR CELLULAR BATH FOR ARM & FOOT.	QTY
<p style="text-align: center;"><u>FOUR CELLULAR BATH FOR ARM & FOOT.</u></p> <ul style="list-style-type: none"> - It is an compact construction design, completely free-standing, out of double paneling glass-fiber material with 2 foot and 2 swiveling arm-bath cells. For application of part, change, increasing and electro-galvanic bath-treatments. 2 removable electrodes per bath cell. - Micro processing controlled panel single electrodes operating, automatic program running, galvanic, impulse and 50 Hz-rectangular current with 2 Hz sinus-overlapping - Digital display - TUV and GS approved with MedGV construction design approval - Voltage: 110V-220V 60 Hz 	1

TRACTION TABLE WITH TRACTION UNIT.**ITEM NO: 15**

Specification For: TRACTION TABLE WITH TRACTION UNIT.	QTY
<p style="text-align: center;">TRACTION TABLE WITH TRACTION UNIT.</p> <ul style="list-style-type: none"> - Adjustable Head and Lumber section - Electric Hi-Lo adjustable from 54.61 to 105.41 cm - Lumber section separates to eliminate friction during lumbar traction - Head section raises to 90 degree and lowers 25 degree - Lower section raises to 90 degree - Intermittent static progressive and cycling programs - Lumber safety switch to call up over 18 kg - Maximum traction force of 90 Kg - Digital readouts for poundage time remaining and number of steps - Key-in of instructions reinforced by audible signals - Hold/Rest continue switch for treatment interruption - Adjustable audible signal at end of treatment - Extended life lithium battery protects memory - Voltage: 110V-220V 60 Hz 	1

SALT BELT TREADMILL.**ITEM NO: 16**

Specification For: SALT BELT TREADMILL.	QTY
<p data-bbox="523 517 906 551" style="text-align: center;"><u>SALT BELT TREADMILL.</u></p> <ul data-bbox="199 577 742 790" style="list-style-type: none">- Adjustable height of handrails 85 to 115cm- Tread surface L/W 157x55cm- Speed: 0-4km/h- Power input: 1kVA- Treadmill fuses: 2x10A- Control: Manual push-buttons- Voltage: 110V-220V 60 Hz	1

AUTO EDAMA REDUCTION WITH LEG & ARM CHAMBERS.**ITEM NO: 17**

Specification For: AUTO EDAMA REDUCTION WITH LEG & ARM CHAMBERS.	QTY
<p><u>AUTO EDAMA REDUCTION WITH LEG & ARM CHAMBERS.</u></p> <ul style="list-style-type: none"> - The sequential moves fluid up to limb in stages, applying pressure segmentally from distal to proximal. It offers varied pressure, adjustable from 30-100 mm Hg. Independent setting allows separate inflation and deflation time from 5 second to 2 minutes. - Made of strong light weight nylon reinforced polyurethane, these garments feature a flexi-walled inflation socket with specially designed connector to assure secure hose retention and prevent air shut off. - Voltage: 110V-220V 60 Hz 	1

MULTIGYM HEAVY DUTY 4 STATION.**ITEM NO: 18**

Specification For: MULTIGYM HEAVY DUTY 4 STATION.	QTY
<p data-bbox="424 555 1007 584" style="text-align: center;"><u>MULTIGYM HEAVY DUTY 4 STATION.</u></p> <ul data-bbox="201 618 1219 734" style="list-style-type: none">- Mounting frame-consisting of 4 panels, various device can be easily mounted- Ideal for group exercises of four persons at a time- Dimension per panel (Width x height) 90 x 240 cm- Lat pulley front seat, leg extension and lying leg curl, PEC DEC and Shoulder press.	1

CPM KNEE HIP AND ANKLE.**ITEM NO: 19**

Specification For: CPM KNEE HIP AND ANKLE.	QTY
<p data-bbox="496 517 932 551" style="text-align: center;"><u>CPM KNEE HIP AND ANKLE.</u></p> <ul data-bbox="199 584 1059 790" style="list-style-type: none">- Length: 63.5 cm- Width: 33 cm- Weight: 10.9 kg- Range of motion: Hip: 4° to 100°, Knee: -10° to 135°, Ankle: -25° to 45°- Patient size: 1.23 m to 1.95 m- Rate of motion: 1.5 to 12 minutes per cycle- Voltage: 110V-220V 60 Hz	1

CPM SHOULDER.**ITEM NO: 20**

Specification For: CPM SHOULDER.	QTY
<p data-bbox="582 555 847 589" style="text-align: center;"><u>CPM SHOULDER.</u></p> <ul data-bbox="199 618 624 853" style="list-style-type: none">- Range of motion:- External rotation: 0 to 85o- Internal Rotation: 0 to 85o- Forward Flexion: 0 to 135o- Extension: 0 to135o- Abduction: 0 to 135o- Rate of motion: 110o per minute- Battery life: 8-10 hours	1

CPM ELBOW.**ITEM NO: 21**

Specification For: CPM ELBOW.	QTY
<p data-bbox="612 517 820 555" style="text-align: center;"><u>CPM ELBOW.</u></p> <ul data-bbox="199 580 788 757" style="list-style-type: none">- Dimensions of actuator unit: 905cm x 38.5 mm- Weight: 2 kg- Rate of motion: 3 minutes per cycle- Reversing force: 4.5 kg low / 8 kg high- Battery life: 8 to 10 hours- Voltage: 110V-220V 60 Hz	1

SHORTWAVE UNIT.**ITEM NO: 22**

Specification For: SHORTWAVE UNIT.	QTY
<p data-bbox="564 517 866 551" style="text-align: center;"><u>SHORTWAVE UNIT.</u></p> <ul data-bbox="201 580 1262 904" style="list-style-type: none">- Short wave therapy device with deeply acting application for specific stimulation of healing processes- Pleasant felt thermo-radiation by highest possible heat-relief of the skin. Specific thermo performances through various electrodes.- Universal adjustable, easy useable, non fatigue supporting arms and flexible silicon cable available every desired application- Working frequency: 27, 12 MHz- HF-Power: 400W- Impulse Power: 400W- Impulse width: 2 ms/0.4 ms- Voltage: 110V-220V 60 Hz	1

ARTERIAL VENOUS IMPULSE SYSTEM.**ITEM NO: 23**

Specification For: ARTERIAL VENOUS IMPULSE SYSTEM.	QTY
<p data-bbox="411 551 1018 584" style="text-align: center;"><u>ARTERIAL VENOUS IMPULSE SYSTEM.</u></p> <ul data-bbox="199 618 944 792" style="list-style-type: none">- Micro-computer system for fully automatic control and safety- Lightweight, slim and highly portable- Acoustically designed for quiet operation- Two Independently adjustable channels- Impulse pressure control- Voltage: 110V-220V 60 Hz	1

MEDICAL LASER 3-COMBY.**ITEM NO: 24**

Specification For: MEDICAL LASER 3-COMBY.	QTY
<p data-bbox="501 555 927 589" style="text-align: center;"><u>MEDICAL LASER 3-COMBY.</u></p> <ul data-bbox="199 618 1201 763" style="list-style-type: none">- NR. 1 Laser guide light 650 nm, 1 mV- NR4 1R. Laser905nm, MOCVD technology- 12W pulsed emission, 24mW average each variable frequency from 1 to 10000Hz, Duration of the laser pulse 100 ns & 200 ns- Voltage: 110V-220V 60 Hz	1

ELECTRONIC TREADMILL.**ITEM NO: 25**

Specification For: ELECTRONIC TREADMILL.	QTY
<p data-bbox="504 555 927 589" style="text-align: center;"><u>ELECTRONIC TREADMILL.</u></p> <ul data-bbox="201 618 1257 770" style="list-style-type: none">- Welded steel frame with all moving parts, Speed adjustable form 1-13km/h, Emergency Stop, Gradient adjustable to 8 degree gas spring- Electronic meter displays speed , distance, time/km, energy consumption, elevation, 20hp DC motor- Voltage: 110V-220V 60 Hz	1

BIKE ERGOMETER+PULSE/WATT+PROGRAMS+POLAR.**ITEM NO: 26**

Specification For: BIKE ERGOMETER+PULSE/WATT+PROGRAMS+POLAR.	QTY
<p data-bbox="288 555 1142 589"><u>BIKE ERGOMETER+PULSE/WATT+PROGRAMS+POLAR.</u></p> <ul data-bbox="201 618 890 734" style="list-style-type: none">- Pulse and effort are programmable- Pulse/Watt Control: in mode "Constant pulse- Resistance range: 60 rmp/270W, / 100 rmp/450 W- Polar transmitter for telemetric heart rate measurement.	1

ROWING MACHINE CONTINUOUS.

ITEM NO: 27

Specification For: <u>ROWING MACHINE CONTINUOUS.</u>	QTY
<p style="text-align: center;"><u>ROWING MACHINE CONTINUOUS.</u></p> <ul style="list-style-type: none">- Smooth sliding seat- Rowing speed in strokes/min- energy consumption- Dimension: 160x40x35 cm	1

STEPPER HEAVY DUTY.**ITEM NO: 28**

Specification For: STEPPER HEAVY DUTY.	QTY
<p data-bbox="528 551 900 584" style="text-align: center;"><u>STEPPER HEAVY DUTY.</u></p> <ul data-bbox="199 618 1225 792" style="list-style-type: none">- Training-computer with permanent digital display of steps per minutes, used calories, watts, pulse (polar system with chest band) and time- Lighted display, power priority, cardio training pulse regulated, performance area 15-155/min especially heavy fly wheel, electro-magnetic resistance system- Dimension: L x W x H 110 x 75 x160 cm- Voltage: 110V-220V 60 Hz	1

MANUMED OPTIMAL COUCH 5 SECTION.**ITEM NO: 29**

Specification For: MANUMED OPTIMAL COUCH 5 SECTION.	QTY
<p data-bbox="395 551 1034 584" style="text-align: center;"><u>MANUMED OPTIMAL COUCH 5 SECTION.</u></p> <ul data-bbox="199 618 986 797" style="list-style-type: none">- Height adjustment (Hydraulic or electric)- Sitting and lying positions- Independently adjustable arm section- Flexion position and Trendelenburg position- Three different full and independently adjustable and gas spring- Voltage: 110V-220V 60 Hz	1

BAR-BELL-RACK WITH CHROMIUM BAR BELLS DUMBELLS 0.5 TO 4 KG.**ITEM NO: 30**

Specification For: BAR-BELL-RACK WITH CHROMIUM BAR BELLS DUMBELLS 0.5 TO 4 KG.	QTY
<u>BAR-BELL-RACK WITH CHROMIUM BAR BELLS DUMBELLS 0.5 TO 4 KG.</u> - Perfect storage of 12 PVC chromium – bar- belts on two levels moveable on 4 swiveling castors	1

ROLL-WEDGES-SEATS-BALL DIFFERENT SIZE.

ITEM NO: 31

Specification For: ROLL-WEDGES-SEATS-BALL DIFFERENT SIZE.	QTY
<u>ROLL-WEDGES-SEATS-BALL DIFFERENT SIZE.</u>	1

DIGFLEX SET OF 5 WITH DIFFERENT RESESTANCE.

ITEM NO: 32

Specification For: DIGFLEX SET OF 5 WITH DIFFERENT RESESTANCE.	QTY
<u>DIGFLEX SET OF 5 WITH DIFFERENT RESESTANCE.</u>	1

**PLATFORM MOUNTED PARALLEL BAR WITH CHILD HANDRAIL
ATTACHMENT AND CENTRAL DIVIDER BOARD.**

ITEM NO: 33

Specification For: PLATFORM MOUNTED PARALLEL BAR WITH CHILD HANDRAIL ATTACHMENT AND CENTRAL DIVIDER BOARD.	QTY
<p style="text-align: center;"><u>PLATFORM MOUNTED PARALLEL BAR WITH CHILD HANDRAIL ATTACHMENT AND CENTRAL DIVIDER BOARD.</u></p> <ul style="list-style-type: none">- Width adjusts form 17" to 26", height 26" to44"- Platform is 40" wide- Length of the Platform 360 cm	1

TRAINING STAIRS.**ITEM NO: 34**

Specification For: TRAINING STAIRS.	QTY
<p data-bbox="571 555 861 589" style="text-align: center;"><u>TRAINING STAIRS.</u></p> <ul data-bbox="199 618 1217 734" style="list-style-type: none">- Frame out of epoxy-resin laminated square steel tube steps out beech-wood, height adjustable and chromium plate hand rail up to 45 cm non-slippery step edges- Size of the platform 66x66 cm, step width 60 cm, step depth 30 cm- At one side 4 steps and other side 3 steps.	1

WOODEN WALL BAR.**ITEM NO: 35**

Specification For: WOODEN WALL BAR.	QTY
<p data-bbox="549 551 880 584" style="text-align: center;"><u>WOODEN WALL BAR.</u></p> <p data-bbox="201 616 635 645">- Height 230 cm and Width 100 cm</p>	1

WALL PULLEY MACHINE.**ITEM NO: 36**

Specification For: WALL PULLEY MACHINE.	QTY
<p data-bbox="512 555 916 589" style="text-align: center;"><u>WALL PULLEY MACHINE.</u></p> <ul data-bbox="199 618 975 707" style="list-style-type: none">- With one handle for wall mounting- Rail-system for wall mounting for pulley exerciser standard- Pulley exerciser are vertical moveable up to a length of 200 cm	1

SHOULDER WHEEL EXERCISE.**ITEM NO: 37**

Specification For: SHOULDER WHEEL EXERCISE.	QTY
<p data-bbox="475 551 954 584" style="text-align: center;"><u>SHOULDER WHEEL EXERCISE.</u></p> <ul data-bbox="199 618 1233 674" style="list-style-type: none">- Metal for wall mounting steering wheel out of metal, height and resistance individually adjustable 100 cm height.	1

QUADRICEPS BENCH.**ITEM NO: 38**

Specification For: QUADRICEPS BENCH.	QTY
<p data-bbox="549 551 884 584" style="text-align: center;"><u>QUADRICEPS BENCH.</u></p> <ul data-bbox="199 618 1238 734" style="list-style-type: none">- Exercise bench with removable and adjustable backrest and two handgrips- Chrome-plated adjustable pendulum arm suitable for leg and knee exercise in seating position- Swinging arm with foot support	1

ORTHOPAEDIC ROLLING MIRROR.**ITEM NO: 39**

Specification For: ORTHOPAEDIC ROLLING MIRROR.	QTY
<p data-bbox="443 551 986 584" style="text-align: center;"><u>ORTHOPAEDIC ROLLING MIRROR.</u></p> <ul data-bbox="199 616 1232 674" style="list-style-type: none">- Mounted in full wooden frame - 4 Pivoting Caster polished mirror glass of 170x70 cm with engraved sections of 10x10 cm	1

MANUMED SPECIAL TILT TABLE 2 SECTION COUCH.**ITEM NO: 40**

Specification For: MANUMED SPECIAL TILT TABLE 2 SECTION COUCH.	QTY
<p data-bbox="304 551 1123 584" style="text-align: center;"><u>MANUMED SPECIAL TILT TABLE 2 SECTION COUCH.</u></p> <ul data-bbox="199 618 746 824" style="list-style-type: none">- Tilting table top from 0 to 90 degree- Fixation rails for belts and straps- Fixed height or electric height adjustment- Battery back-up- Large Wheels to easy move- Durable, hygienic and washable upholstery- Voltage: 110V-220V 60 Hz	1